

Technical Datas:

Name	LED High Bay								Waterproof, Dustproof LED High Bay
Part Number	HB-AL-160W		HB-AL-120W		HB-AL-80W		HB-AL-60W		HB-DP-60W
Power consumption	160W		120W		80W		60W		60W
Typical Replace	400W MH		250W MH		160W MH		130W MH		130W MH
Light Output (Lumens)	14400 lm		10800 lm		7200 lm		5400lm		5400lm
LED Efficacy	90lm/w		90lm/w		90lm/w		90lm/w		90lm/w
Fixture Efficiency	75lm/w		75lm/w		70lm/w		70lm/w		70lm/w
Housing & Lampshade	aluminium	PC	aluminium	PC	aluminium	PC	aluminium	PC	aluminium alloy
Color	silver gray	transparent	silver gray	transparent	silver gray	transparent	silver gray	transparent	silver gray
Size(mm)	hook:φ500×442 hanging plate:φ500×400	hook:φ500×611 hanging plate:φ500×561	hook:φ500×442 hanging plate:φ500×400	hook:φ500×611 hanging plate:φ500×561	hook:φ380×359 hanging plate:φ380×315	hook:317*408 hanging plate:φ317*365	hook:φ380×359 hanging plate:φ380×315	Hook:φ317*408 hanging plate:φ317*365	hook:φ358×360 hanging plate:φ380*310
Package Dimension	570×570×430mm	570×570×595mm	570×570×430mm	570×570×595mm	440×440×340mm	370×370×420mm	440×440×340mm	370×370×420mm	405×405×345mm
G.W/N.W	6.5kg/2.9kg	7.5kg/4.1kg	6.5kg/2.9kg	7.5kg/4.1kg	3.1kg/1.1kg	3.2kg/1.36kg	3.1kg/1.1kg	3.2kg/1.36kg	3.6kg/2.2kg
Input Voltage	90VAC~260VAC								
AC Power Factor	98%								
DC Power Efficiency	94.00%								
Color Temperature	2700K~ 6500K								
Beam Angle	120°								
CRI	Ra>80								
Working Temp.	-40℃ ~ +50℃								
Lifespan	50000 h								
Certifications	CE/RoHS/ETL								
Mounting style	Hook or Hanging plate								
Lens reflector	Aluminum alloy								
IP Rating	IP20								IP54