HITECNICO LED Luminaires







Features & Benefits:

- Excellent modular design
- Top grade LED chips from Philips Lumileds
- Reliable and high efficiency driver from Mean Well
- Universal full range input 90-305V~; 50/60Hz
- IES file is available for Dialux simulation
- Shock and vibration resistant, water and dust proof IP66
- Symmetric light distribution for wide applications
- Huge energy saving up to replace 350W ~ 400W HPS or MH
- Eco-friendly with no mercury, no lead, no flickers
- Long lifespan for over 50,000 hours
- Easy installation with tool-free maintenance
- The whole lamp up to 5 years warranty

Dimension Drawing (Unit:mm)





Specifications:

Model No. HTI-TS-F160A Power 160W Philips Lumileds **LED Chip** Mean Well **Power Supply** Efficiency ≥100lm/W Lumen Output ≥16000lm Input Voltage AC 90-305V 50/60Hz Frequency Power Factor (PF) >0.95 **Working Temp** -40 ℃~ 50 ℃ Ra≥75 **Mounting Way** U-shape Bracket **IP Rating** IP66 Lifespan ≥50,000hours Warranty 8 years Material **Aluminums Alloys** Color Temp 5700K, 6500K, 4000K, 3000K **Light Distribution** Symmetric **LED Drive Current** 0.85A 392 × 304 × 196 mm Dimension(L×W×H) Net Weight 7.15kg Finish Color Black (White is optional)

Applications:

Parking Area Tunnel Stadium High Mast Square






Optics: Type I

-150 -/+180 150 -120 -90 -60 -30 1500 30 0

Type V-60D



HITECNICO, quality you can trust!

www.hitecnico.com