




## 閉端端子 Closed-End Wire Connectors

- ◆ Insulating material:  
Polyamide 66 (Nylon 66),  
Flame-retardant to UL 94V-2
- ◆ Sleeve : Brass or Aluminum, Tin-Plated
- ◆ Crimping tools:  
Air Tools - MR30A for CE1, CE1X, CE2, CE2X and CE5, CE5X  
- EZUMI AC-510D for CE2, CE2X  
Hand Tools - Lobster AK-25 for CE1, CE1X, CE2, CE2X  
and CE5, CE5X  
- Lobster AK-20 for CE8  
- EZUMI #7A for CE2, CE2X



### 尺寸 (Dimensions)

型號 Model	A (m.m)	B (m.m)	C (m.m)
CE1	2.60	7.80	18.00
CE2	3.10	9.50	20.00
CE5	4.40	12.50	25.50
CE8	5.30	14.30	27.70



型號 Model	顏色 Color	適用電線 Wire Range	額定電氣規格 Electrical Ratings	安規認證/Approval			包裝單位 Packing
				UL E113650	CSA LR68461		
CE1	原色 Nature	#22-#18AWG, Cu	電壓: 300 Volt Max. 溫度: 105°C(221°F)				1,000 Pcs/Bag 30,000 Pcs/Ctn
CE1X							
CE2	原色 Nature	#22-#14 AWG, Cu	電壓: 300 Volt Max. 溫度: 105°C(221°F)				1,000 Pcs/Bag 20,000 Pcs/Ctn
CE2I							
CE2X							
CE5	原色 Nature	#22-#10 AWG, Cu	電壓: 300 Volt Max. 溫度: 105°C(221°F)				1,000 Pcs/Bag 10,000 Pcs/Ctn
CE5I							
CE5X							
CE8	原色 Nature	#16-#10 AWG, Cu	電壓: 300/600 Volt Max. 溫度: 105°C(221°F)				500 Pcs/Bag 6,000 Pcs/Ctn

專利產品 仿冒必究