




## » 端子台(平底型) Terminal Block(Flat Base Type)

- ◆ Base With flat base
- ◆ Housing Material Polyamide 66 (Nylon 66), Flame-retardant to UL 94V-2
- ◆ Temperature Rating 105 °C (UL), -30 °C to T110 °C, T140C(IEC)
- ◆ Terminal Insert Brass metal alloy, nickel plated
- ◆ \* Steel provided with a brass strip.
- ◆ Wire Protector (DS) Stainless spring steel
- ◆ Screw Steel, zinc plated
- ◆ Poles Available 2 to 12 poles
- ◆ Available in pre-cutting to specified number of poles.
- ◆ Available in specific packing and private labeling.
- ◆
- ◆
- ◆



### 規格尺寸 (Dimensions)

型號 Model	訂單編號 Cat.No.	適用電線 / Wire Range		螺絲 Screw	尺寸 / Dimensions(mm)						包裝單位 Packing
		Cross-Sec.	(AWG,Cu)		A	B	C	D	E	F	
PA8	PA8F	1.5mm <sup>2</sup>	#22-#12 Sol/Str	M2.6x5	96.20	16.40	12.70	8.20	2.90	2.8±0.1	50 Pcs/Bag 500 Pcs/Ctn
PA8DS	PA8FDS	1.5mm <sup>2</sup>	#22-#12 Sol/Str	M2.6x5	96.20	16.40	12.70	8.20	2.90	2.8±0.1	50 Pcs/Bag 500 Pcs/Ctn
PA10	PA10F	2.5mm <sup>2</sup>	#22-#10 Sol #14-#10 Str	M3.0x6	117.2	20.20	15.80	10.00	3.60	3.2±0.1	50 Pcs/Bag 500 Pcs/Ctn
PA10DS	PA10FDS	2.5mm <sup>2</sup>	#20-#10 Sol #22-#12 Str	M3.0x6	117.2	20.20	15.80	10.00	3.60	3.2±0.1	50 Pcs/Bag 500 Pcs/Ctn

### 安規認證 (Approvals)

型號 Model	美國 E152546	加拿大 LR79786	德國 UL	芬蘭 F	瑞典 S	挪威 N	丹麥 D	荷蘭 KEMA KEUR	比利時 CECC	奧地利 OVE	瑞士 S	意大利 Y	中國 CCC
PA8 PA8DS	300V 20A	600V 20A	450V 17.5A	450V 17.5A	450V 17.5A	450V 17.5A	450V 17.5A	450V 17.5A	450V 17.5A	450V 17.5A	450V 17.5A	450V 17.5A	400V 17.5A
PA10 PA10DS	300V 30A	600V 30A	450V 24A	450V 24A	450V 24A	450V 24A	450V 24A	450V 24A	450V 24A	450V 24A	450V 24A	450V 24A	400V 24A

\* 特殊產品，仿照必求