




Push-In Wire Connectors

For use with rigid/solid conductors

- **Housing:** Polycarbonate (PC) and Polyamide 66 (PA 66), flame-retardant to UL 94V-0 Working temperature: T110 (IEC)
- **Insert:** Steel plate with copper strip, tin-plated Stainless spring steel
- Provide about 25% space-saving than old types.
- Color-coded for quick and easy identification.
- Can be supplied under private label packaging.



Around 25% space-saving



Model	Poles	Color	Rated	Packing	Cat. No.
PC2252	2	Red	IEC: 24 A, 450 V 1 - 2.5 mm ² Rigid Single-core Rigid Multi-core	Ctn of 10,000 (10 bags, 1,000 ea.)	PC2252-01
				Box of 100	PC2252-00
PC2253	3	Orange	IEC: 24 A, 450 V 1 - 2.5 mm ² Rigid Single-core Rigid Multi-core	Ctn of 8,000 (8 bags, 1,000 ea.)	PC2253-01
				Box of 100	PC2253-00
PC2254	4	Yellow	IEC: 24 A, 450 V 1 - 2.5 mm ² Rigid Single-core Rigid Multi-core	Ctn of 5,000 (10 bags, 500 ea.)	PC2254-01
				Box of 100	PC2254-00
PC2255	5	Grey	IEC: 24 A, 450 V 1 - 2.5 mm ² Rigid Single-core Rigid Multi-core	Ctn of 5,000 (10 bags, 500 ea.)	PC2255-01
				Box of 100	PC2255-00
PC2258	8	Black	IEC: 24 A, 450 V 1 - 2.5 mm ² Rigid Single-core Rigid Multi-core	Ctn of 2,500 (10 bags, 250 ea.)	PC2258-01
				Box of 50	PC2258-00